

# MAT7

## Chopped Strand Mat



### CHOPPED STRAND MAT FOR PANEL APPLICATIONS

#### Product Description:

MAT7 powder bonded chopped strand mat has been developed from E-glass for fiber sandwich panel, flat and corrugated laminate applications.




#### Features and Benefits:

- Manufacturing in accordance with ISO 9001:2015 conditions
- Homogenous weight distribution
- Fast wet-out
- Easy shaping
- Easy impregnation
- Low resin consumption
- High tensile strength

#### Product Specifications:

<b>Glass Type</b>	E	<b>Sizing Type</b>	Silane
<b>Weight per Unit Area (g/m<sup>2</sup>)</b>	100/150/175/225/300/ 375/450 ± 5%	<b>Split Tex (g/1000 m)</b>	Nom. 15
<b>Fiber Diameter (μ)</b>	Nom. 14	<b>Length of Chopped Strand (mm)</b>	50
		<b>Resin Compatibility</b>	Unsaturated Polyester

#### End-use Markets:

-  Panel Applications
-  Sandwich Panels
-  Colored Panels

#### Roll Dimensions:

Inner Diameter (mm): 100  
External Diameter (mm): 410

#### Packing Information:

<b>Packaging</b>	With / Without Paper Body / With Paper Box
<b>Number of Rolls Per Pallet</b>	Between 12 - 30
<b>Pallet Dimensions (cm)</b>	110 x 146
<b>Pallet Height (cm)</b>	Depend on Order
<b>Average Pallet Net Weight (kg)</b>	400 - 1100



Please scan the QR code  
for more detailed  
packaging information.

#### Storage Conditions:

Product should be stored in dry area at room temperature and relative humidity of approx 65%. Product should be conditioned for 24 hours in the work area prior to use. In case of partial usage, package should be re-sealed.

Form No: EN-3126-1

Revision Date: 03.2023