



ŞİŞECAM MULTI END ROVING

MULTI END ROVING FOR CHOPPING APPLICATIONS AND PANEL PRODUCTION

KCR10

KCR10 multi end roving is made from E-Glass

Features and Benefits

- Good unwinding
- Good choppability and uniform fiber dispersion
- Fast wet-out,
- Very low fuzz generation during processing
- Low resin consumption

Designed for continuous panel production and chopping applications.



PRODUCT SPECIFICATION

Glass Type	E	Moisture Content (%)	max. 0,1
Roving Tex (g/1000m)	2400 ± %5	Sizing Content (%)	0,85 ± 0,20
Filament Diameter (µ)	Nom. 13	Sizing Type	Silane
Split Tex (g/1000m)	Nom. 40	Resin Compatibility	Unsaturated Polyester, Epoxy

BOBBIN DIMENSIONS AND PACKAGING

Inner Diameter (mm)	External Diameter (mm)	Weight (kg)	Height (mm)
100	300	Nom. 20	260

Packaging	Number of bobbins per pallet	Number of layers per pallet	Pallet Dimensions (cm)	Pallet Height (cm)	Pallet Net Weight (kg)	Number of ends	Number of bobbins per layer
Bulk Packaging	48	4	96 x 128	125	1100	0-1-2-3-4	12

Product should be stored in dry area at room temperature and relative humidity of approx 65%

Product should be conditioned for 24 hours in the work area prior to use.
In case of partial usage, package should be re-sealed.

ŞİŞECAM ELYAF SANAYİİ A.Ş.

İçmeler Mahallesi, D-100 Karayolu Caddesi,
No: 44B 34947 Tuzla İstanbul Turkey

T +90 850 206 3635
F +90 850 206 4583

www.sisecamchemicals.com